

## AIR LIQUIDE

### Pressure Regulators, Bottle Pressure Regulators, Relief Valves Stainless Steel SS 316L - Brass

#### Pressure Regulators



**DLM 240-15-50**

P/N AL423321

**Brass**

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 0.5 up to 15 bar

Flow capacity: 50 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -20°C up to +50°C

**DLM 240-50-100**

P/N AL423308

**Brass**

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 5 up to 50 bar

Flow capacity: 100 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -20°C up to +50°C



**DIM 240-3-5**

P/N AL422501

**SS 316 L**

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 0.3 up to 3 bar

Flow capacity: 5 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -20°C up to +50°C

**DIM 240-30-30**

P/N AL415995

**SS 316 L**

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 5 up to 30 bar

Flow capacity: 30 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -20°C up to +50°C



**BSI 50-1-2**

P/N AL423103

**SS 316 L**

Single stage

Inlet pressure: max. 50 bar

Outlet control range: 0.05 up to 1 bar

Flow capacity: 2 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -20°C up to +50°C

## Bottle Pressure Regulators



### **HBD 240-10-12**

P/N AL422163

#### **Brass**

Dual stage

Inlet pressure: max. 240 bar

Outlet control range: 0.1 up to 7 bar

Flow capacity: 9.4 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -40°C up to +74°C



### **HBD 240-10-12-S**

P/N AL422164

#### **SS 316 L**

Dual stage

Inlet pressure: max. 240 bar

Outlet control range: 0.1 up to 7 bar

Flow capacity: 9.4 Nm<sup>3</sup>/h (N<sub>2</sub>)

Operating temperature: -40°C up to +74°C

## Relief Valves



### **SV 805 ES - SS 316 L**

P/N AL421145

#### **SV 805 MS - brass**

P/N AI421144

Connections

Inlet: G3/8

Outlet: for tube ø6mm

Outlet pressure to atmosphere 16 bar (others on request)